

PCT/EP200 4 / 0 0 4 0 0 7

REC'D 26 MAY 2004	
WIPO	PCT

INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road 14 APR 2004
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 2 March 2004

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office
Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

JNR/HG/PB60091P

2. Patent application number

(The Patent Office will fill in his part)

19APR03 E801248-2 001030
P01/7700 0.00-0308969.5

0308969.5

17 APR 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Glaxo Group Limited
Glaxo Wellcome House, Berkeley Avenue,
Greenford, Middlesex UB6 0NN, Great Britain

Patents ADP number (*if you know it*) 00473587003

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Capsules

5. Name of your agent (*if you have one*)

Corporate Intellectual Property

"Address for service" in the United Kingdom to which all correspondence should be sent

(including the postcode)

GlaxoSmithKline
Corporate Intellectual Property (CN9 25.1)
980 Great West Road
BRENTFORD
Middlesex TW8 9GS

Patents ADP number (*if you know it*)

05321846001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (*if you know it*) the or each application number

Country	Priority application number (<i>if you know it</i>)	Date of filing (day / month / year)
---------	--	--

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)
-------------------------------	--

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer yes if:*


- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is named as an applicant, or
- c) any named applicant is a corporate body

See note (d)

Patents Form 1/77

Patents Act 1977
(Rule 16)

The
Patent
Office



1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office
Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

JNR/HG/PB60091P

2. Patent application number

(The Patent Office will fill in his part)

19APR03 E801248-2 001030
P01/7700 0.00-0308969.5

0308969.5

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Glaxo Group Limited
Glaxo Wellcome House, Berkeley Avenue,
Greenford, Middlesex UB6 0NN, Great Britain

Patents ADP number (*if you know it*) 00473587003

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Capsules

5. Name of your agent (*if you have one*)

Corporate Intellectual Property

"Address for service" in the United Kingdom to which all correspondence should be sent
(*including the postcode*)

GlaxoSmithKline
Corporate Intellectual Property (CN9 25.1)
980 Great West Road
BRENTFORD
Middlesex TW8 9GS

Patents ADP number (*if you know it*) 08321846001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (*if you know it*) the or each application number

Country	Priority application number (<i>if you know it</i>)	Date of filing (<i>day / month / year</i>)
---------	--	---

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (<i>day / month / year</i>)
-------------------------------	---

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer yes if:*

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is named as an applicant, or
- c) any named applicant is a corporate body

See note (d)

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawings

11

3

1

2

DL
only

10. If you are also filing any of the following, state how many against each item.

Priority Documents


Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. We request the grant of a patent on the basis of this application.
Signature  Date 17-Apr-03
J N Rice

12. Name and daytime telephone number of person to contact in the United Kingdom
J N Rice 01279 644508

Warning

After an application for a Patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- For details of the fee and ways to pay please contact the Patent Office.

CAPSULES

The present invention relates to chain linked capsules and is particularly, although not exclusively, concerned with such capsules which are adapted to contain
5 therein a powder product, for example a medicinal powder product for a person to inhale using a dry powder inhalation device ("DPI" for short).

DPIs are well established for use in treating respiratory diseases. As an example, there is the DISKUS (RTM) device of GlaxoSmithKline. In general, the
10 pharmaceutical composition is formulated as a respirable powder product and the powder product is divided into a plurality of unit doses, each dose contained in its own sealed enclosure, for example in blisters on a dosing strip. When using prior art inhalation devices, an enclosure on a dosing strip in the inhalation device is opened by an opening mechanism of the inhalation device and the powder dose in
15 the enclosure can then be entrained into a patient's respiratory tract by an airflow generated through the device by the patient inhaling at a mouthpiece of the device.

Some sealed enclosures used in DPIs are difficult to fill with a unit dose of the
20 pharmaceutical powder product. Therefore there has been a tendency to make the enclosures bigger than they need to be, and adding a filler to the pure drug powder, such as lactose powder, to bulk out the powder product. The filling of larger enclosures is easier. However, GB0227128.6, filed 20th November 2002, provides a capsule for holding a powder product which has a mechanism for
25 facilitating the filling of it with the powder product.

The capsule disclosed in GB0227128.6 will generally be small enough to dispense active ingredients without the need to bulk out the powder with a lactose or other filler as much as before or even at all. Due to its small size, the capsule is referred
30 to as a "microcapsule".

The handling of the capsule, however, can be difficult or fiddly. The present invention facilitates the handling of the capsule, in particular once filled, for example to make it easier to manipulate a number of them when loaded in a DPI.

- 5 The present invention provides chain linked capsules. Preferably the present invention provides chain linked microcapsules, for example of a length of no more than about 15mm, preferably no more than about 6mm, and a width of no more than about 8mm, preferably no more than about 5mm. Preferably the chain linked capsules form a loop, e.g. an endless loop like a bicycle chain.

10

By chain linking the capsules (or microcapsules), they are easier to manipulate during filling, or during use in a DPI, than separate capsules or microcapsules.

The present invention further provides a capsule and a chain link for the capsule.

- 15 Preferably the chain link is engageable with the capsule, for example by insertion of a protrusion of the chain link into an opening in the capsule. However it may be integral with the capsule or it may be engaged with the capsule.

- 20 Preferably the chain link extends from the capsule. Preferably it extends from a base of the capsule.

Preferably the capsule is generally cylindrical.

25

Preferably the chain link extends generally radially outward from the capsule.

Preferably the capsule comprises a chamber for containing a powder product.

Preferably the capsule comprises a sleeve which is provided with an internal chamber for holding a powder product within the capsule.

30

Preferably the sleeve comprises a first opening at a first end thereof and a second opening at an opposite end thereof.

Preferably the capsule comprises the sleeve and a piston.

Preferably the capsule comprises two chambers separated by a flange portion
5 within the sleeve, the first of the chambers being for containing the powder product.

Preferably the sleeve is a single piece component.

10 Preferably the piston is adapted to extend within the sleeve from the first end, through the first chamber and the flange portion, and into the second chamber.

Preferably the piston comprises a cap and a rod. Preferably these parts are integrally formed.

15

Preferably the piston can seal the first chamber by forming a seal against the first opening and the flange portion.

Preferably the sleeve and the piston are adapted to be displaced between a
20 discharging position or state in which both the chamber of the capsule that is adapted to contain a powder product is open to the outside environment and a vent provided in the base of the chamber is open for allowing powder product from within the chamber to be sucked out of the chamber through the first opening to the outside environment and a sealing state in which both the chamber is sealed
25 from the outside environment and the vent is closed.

Preferably the base is the flange portion that separates the two chambers and the vent is provided through the flange portion.

30 Preferably, in the sealing state, the piston closes the vent to isolate the two chambers from each other.

Preferably the capsule can be placed into a third state in which the chamber is open to the outside environment at the first opening and there is a partial seal at the vent. This partial seal will be gas pervious but will entrap powder product, thereby enabling a vacuum to be applied at the vent to create an airflow from the first opening, through the chamber, towards the vent for entraining powder product from a powder product cloud in the outside environment into the chamber. The powder product will not pass beyond the vent, thereby filling the chamber with powder product.

- 10 Preferably the partial seal at the vent is formed with the piston extending through the flange portion between the two chambers. Preferably, the piston has a circumferential array of longitudinal channels formed in the portion of the outer surface of the piston that is within the flange portion.
- 15 Preferably the second opening of the sleeve is adapted to engage with a correspondingly sized protrusion on a chain link for rotatably connecting the capsule to the chain link.

Preferably the protrusion is a tubular portion having a hole therethrough.

20

Preferably the chain link is pivotally connected to the capsule, or another capsule, at one end of the chain link.

- Preferably the chain link is pivotally connectable to capsules at both ends of the chain link.
- 25

Preferably a flange extends outwardly from the second end of the sleeve of the capsule. Preferably a tubular portion is provided at an outermost end of the flange. The flange may be integrally formed with the sleeve.

30

Preferably the tubular portion has a diameter that is substantially equal to or slightly greater than the diameter of the second opening of the capsule.

Preferably the tubular portion is inserted into an open end of an adjacent, identical, capsule to form chain linked capsules.

- 5 Preferably the connection is a push fit. However, the connection may be a loose fit.

Preferably the inside diameter of the tubular portion is larger than the distal end of the piston.

10

The chain link may be a separately formed component comprising two tubular portions.

- 15 Preferably the two tubular portions are provided at the ends of a flange. Preferably the flange extends between the bases of the tubular portions.

Preferably a first tubular portion is of a first diameter and the second tubular portion is of a second diameter.

- 20 Preferably both tubular portions are hollow.

Preferably the second tubular portion has an internal diameter corresponding generally to the outside diameter of the first tubular portion.

25

Preferably the first tubular portion of a first chain link fits within a second tubular portion of an adjacent, identical, chain link.

- 30 Preferably the second tubular portion has an outside diameter corresponding generally with the diameter of the second opening of the capsule.

Preferably a plurality of capsules and chain links are connected together to form chain linked capsules.

Preferably chain linked capsules are provided within a channel. The channel may
5 be a closed channel, i.e. with both a base and a roof, or the like, and/or an endless channel.

Preferably the capsules and chain links are made of a plastics material.
Preferably they are moulded.

10

The present invention further provides an inhalation device having chain linked, medicinal powder-containing, capsules. Preferably, the capsules are linked in an endless chain.

15 Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 is a part sectional side view of a capsule for a powder product as disclosed in GB0227128.6 for use in the present invention with the powder product
20 contained in a sealed chamber defined between a piston and a sleeve;

Figure 2 is a cross-sectional view of the capsule of Figure 1 in a discharge position relative to the sleeve;

25 Figure 3 shows a plurality of capsules in accordance with the present invention in an endless channel;

Figure 4 shows a pair of capsules in accordance with the present invention; and

30 Figure 5 shows an alternative embodiment of the present invention.

Referring to Figures 1 and 2 there is shown a generally cylindrical capsule 10 filled with a powder product 12. The capsule 10 has particular application for dry powder products, more particularly for holding a unit dose of a dry powder pharmaceutical formulation or medicament for inhalation by a patient. The capsule 10 may be used in a dry powder inhalation device (a DPI).

The capsule 10 of Figures 1 and 2 is described in detail in GB0227128.6, the entire contents of which are incorporated herein by way of reference.

10

The capsule 10 comprises a piston 14 and a sleeve 16.

The sleeve 16 is a generally tubular or cylindrical member that defines a generally cylindrical passage 18 therethrough.

15

The passage 18 defines two chambers 19a, 19b separated by a flange portion 21. The passage 18 has two ends 20, 24. The flange portion 21 is between the two ends 20, 24.

20 The piston 14 can be positioned selectively within the sleeve 16 to provide various states for the capsule 10: a filling state, a sealing state and a dispensing state.

A sealing state is shown in Figure 1. The first chamber 19a is sealed closed; the first end 20 of the passage 18 and the flange portion 21 are both sealed by the piston 14. The second end 24 of the passage 18, however, is open.

A dispensing state is shown in Figure 2. The first chamber 19a is no longer sealed. The first end 20 is open and a vent 23 between the flange portion 21 and the piston 14 is open. The second end 24 also still is open. Powder 12 contained within the first chamber 19a can therefore be vented 22 from within the capsule 10 through the first end 20 to the outside environment.

In a filling state, not shown, the piston 14 is positioned halfway between its positions in the dispensing state and the sealing state. In this position, the first end 20 of the passage 18 will still be open, but the vent 23 between the piston 14 flange portion 21 will be partially sealed (see GB0227128.6). The piston 14 has a
5 circumferential array of longitudinal channels 25 formed in the portion of the outer surface of the piston 14 that will lie within the flange portion 21 in the filling state. These channels 25 allow air to pass through the vent 23, but will not allow powder 12 to pass through the vent 23. Therefore, the first chamber 19a can be filled by drawing air having powder 12 dispersed therein through the passage 18 extending
10 through the capsule 10 from the first end 20 of the passage 18 to the second end 24 of the passage, when the capsule 10 is in its filling state.

The piston 14 comprises a cap 27 and a rod 29. The cap 27 is for sealing the first end 20 of the passage 18 when the piston 14 is pushed fully into the passage 18,
15 as shown in Figure 1. The rod 29 extends axially through the passage 18 and is for selectively opening the vent 23 in the flange portion 21.

The rod 29 comprises various portions. Starting at its distal end 28 there is a narrowed portion 40. Then there is the circumferential array of longitudinal
20 channels 25. Finally there is a smooth sided piston portion 42. These, when positioned within the flange portion 21, select the sealing state of the vent 23 in the flange portion 21: open, partially sealed and sealed, respectively.

The length of the rod 29 is such that, in the sealing state, the distal end 28 of the
25 piston 14 does not protrude beyond the second end 24 of the sleeve 16.

The rod and the passage are generally round in shape. Other shapes may, however, be used. For a round shape, the distal end 14 of the rod 29 has an outer diameter D_5 that is much smaller than the inner diameter D_1 of the passage 18 at
30 the second end 24 of the sleeve 16. This means that there is an annular space 31 at the second end 24 of the sleeve 16 even when the piston 14 is fully pushed into

the sealing state shown in Figure 1. This annular space 31, in accordance with the present invention, allows a chain link to be used to form chain linked capsules.

Figure 3 shows a plurality of chain linked capsules 10 in an endless channel 30 such as one in a DPI, not shown. Such an endless channel 30 may be provided for retaining a plurality of capsules 10 for use, one at a time, by the DPI.

Referring to Figure 4, a preferred arrangement for the chain link 32 is shown.

10 The capsule 10 is generally as described with reference to Figures 1 and 2. However, a flange 34 extends outwardly from the second end 24 of the sleeve 16 of the capsule 10 to a tubular portion 36. The flange 34 and the tubular portion 36 form the chain link 32.

15 The flange 34 is integrally formed with the sleeve 16. Referring to Figure 5, however, the chain link 32 may be a separately formed component comprising a flange 34 and two tubular portions 36, 38.

Referring back to Figure 4, the flange 34 has a tubular portion 36 at its outermost end. The tubular portion 36 has an outer diameter D_2 that is substantially equal to the inner diameter D_1 of the annular space 31, i.e. the passage 18 extending through the sleeve 16 of the capsule 10. The tubular portion 36 can therefore be inserted into the annular space 31 at the second end 24 of an adjacent capsule 10 to chain link capsules together.

25

By making the connection a push fit between the tubular portion 36 and the annular space 31, relative rotation will still be achievable but the separation of the two connected capsules 10 will be difficult. Therefore, the chain linked capsules 10 would be able to travel along the endless channel 30 without being retained in the channel 30 from above.

30

Instead of a push fit connection, however, the capsules could be connected with a loose fit connection. This has the advantage of having a reduced resistance to flexing around the curves of the channel 30. However, there would be an increase in the tendency for adjacent capsules to separate, thereby breaking the chain link.

5 By making the channel 30 a closed channel, i.e. with both a base and a roof, or the like, relative axial movement between adjacent capsules 10 would be eliminated. This would prevent inadvertent separation of adjacent capsules 10.

The tubular portion 36 has a hole 44 extending therethrough so that the distal end
10 28 of the piston 14 can be fitted therein. The inside diameter D_6 of the hole 44 is larger than the outer diameter D_5 of the distal end 28 of the piston 14 so that relative rotation of adjacent capsules 10 will not cause the piston 14 to be rotated relative to its sleeve 16. This will help to prevent inadvertent dispensing of the powder 12 from within the capsule 10.

15 Referring again to Figure 5, a separate chain link 32 is shown. In this embodiment, the chain link 32 has two tubular portions 36, 38. The two tubular portions 36, 38 are at opposed ends of a flange 34. The flange extends between the bases of the two tubular portions 36, 38.

20 The first tubular portion 36 has a first outside diameter D_2 . The second tubular portion 38 has a second outside diameter D_4 . Both tubular portions have holes 44 extending therethrough.

25 The second tubular portion 38 has an internal diameter D_3 corresponding generally to the outside diameter D_2 of the first tubular portion 36. The first tubular portion 36, therefore, has a smaller diameter than the second tubular portion 38 and it fits, rotatably, within a second tubular portion 38 of an adjacent chain link 32.

30 The second tubular portion 38 has an outside diameter D_4 corresponding generally with the inner diameter D_1 of the passage 18 in the sleeve 16 of the capsules 10. Therefore, the second tubular portion 38 of the chain link 32 will fit, rotatably,

within the passage of the capsule 10. This will allow a plurality of capsules 10 and chain links 32 to be used to form chain linked capsules in accordance with the present invention.

- 5 The capsules 10 and chain links 32 are preferably made of a plastics material and they can be moulded, e.g. by injection moulding, micro moulding etc..

The capsules 10 may have a length L in the range of about 5mm to about 15mm, an outer diameter D in the range of about 3mm to about 8mm, and the passage 18
10 extending through the capsule 10 may have an inner diameter D_1 in the range of about 1mm to about 6mm. In other words, the capsules 10 may be microcapsules. Such capsules 10 are particularly suited for holding unit doses of pharmaceutical powder in the range of about $2\mu\text{g}$ to about 30mg. The capsules 10 may each
15 contain a unit dose of pure active drug substance, or a blend of pure active drug substances, in the range of about $2\mu\text{g}$ to about $250\mu\text{g}$ (i.e. no bulk filler), or a bulked-out unit dose of pharmaceutical powder up to about 30mg.

For a small unit dose of pharmaceutical powder, for instance in the range of about $2\text{-}250\mu\text{g}$, it is preferable for the capsule length L to be in the range of about 5mm
20 to about 6mm, the outer capsule diameter D to be in the range of about 3mm to about 5mm, and the inner diameter D_1 of the passage 18 to be in the range of about 1mm to about 3mm, more preferably about 2mm.

It will of course be understood that the present invention has been described
25 above purely by way of example. Modifications and developments may be made within the scope of the invention as defined in the claims appended hereto.

Moreover, use of terms such as "about" etc. in relation to values of parameters of the invention is meant to encompass the exact parameter value as well as minor
30 deviations therefrom.

CLAIMS

1. Chain linked capsules.
2. Chain linked capsules wherein the capsules have a length of no more than
5 about 15mm and a width of no more than about 8mm.
3. A capsule and a chain link for the capsule.
4. The capsule and chain link of claim 3, wherein the capsule has a length of
no more than about 15mm and a width of no more than about 8mm.
5. The capsule and chain link of claim 3 or claim 4, wherein the chain link
10 extends from a base of the capsule.
6. The capsule and chain link of any one of claims 3 to 5, wherein the capsule
is generally cylindrical.
7. The capsule and chain link of claim 6, wherein the chain link extends
generally radially outward from the capsule.
- 15 8. The capsule and chain link of any one of claims 3 to 7, wherein the capsule
comprises a sleeve which is provided with an internal chamber for holding a
powder product within the capsule.
9. The capsule and chain link of claim 8, wherein the sleeve comprises a first
opening at a first end thereof and a second opening at an opposite end thereof.
- 20 10. The capsule and chain link of any one of claims 3 to 9, wherein the capsule
comprises two chambers separated by a flange portion, the first of the chambers
being for containing a powder product and the second of the chambers being for
connecting a chain link thereto.
11. The capsule and chain link of any one of claims 3 to 10, wherein the
25 capsule comprises a sleeve and a piston.

12. The capsule and chain link of claim 10 and claim 11, wherein the piston is adapted to extend within the sleeve from a first end thereof, through the first chamber and the flange portion, and into the second chamber.

13. The capsule and chain link of claim 11 or claim 12, wherein the sleeve and
5 the piston are adapted to be displaced between a discharging position or state in which both a chamber of the capsule adapted to contain a powder product is open to the outside environment and a vent provided in the base of the chamber is open for allowing powder product from within the chamber to be sucked out of the chamber through a first opening to the outside environment and a sealing state in
10 which both the chamber is sealed from the outside environment and the vent is closed.

14. The capsule and chain link of claim 13, wherein the base is a flange portion separating two chambers and the vent is provided through the flange portion.

15. The capsule and chain link of claim 14, wherein, in the sealing state, the
15 piston closes the vent to isolate the two chambers from each other.

16. The capsule and chain link of any one of claims 13 to 15, wherein the capsule can be placed into a third state in which the chamber is open to the outside environment and there is a partial seal at the vent, the partial seal being gas pervious but powder product impervious.

20 17. The capsule and chain link of claim 16, wherein the piston has a circumferential array of longitudinal channels formed in a portion of the outer surface of the piston.

18. The capsule and chain link of any one of claims 3 to 17, wherein the capsule comprises an opening at an end thereof of a size corresponding with a
25 protrusion on the end of the chain link.

19. The capsule and chain link of claim 18, wherein the protrusion is a tubular portion having a hole therethrough.

20. The capsule and chain link of any one of claims 3 to 19, wherein the chain link is pivotally connected to the capsule at one end of the chain link.
21. The capsule and chain link of any one of claims 3 to 19, wherein the chain link is integral with the capsule.
- 5 22. The capsule and chain link of any one of claims 3 to 19, wherein the chain link is pivotally connectable to a capsule at both ends of the chain link.
23. The capsule and chain link of claim 22, wherein the chain link comprises two tubular portions provided at ends of a flange.
24. The capsule and chain link of claim 23, wherein the first tubular portion is of
10 a first diameter and the second tubular portion is of a second diameter.
25. The capsule and chain link of claim 24, wherein both tubular portions are hollow, the second tubular portion having an internal diameter corresponding generally to the outside diameter of the first tubular portion.
26. The capsule and chain link of claim 25, wherein the second tubular portion
15 has an outside diameter corresponding generally with the diameter of an opening in an end of the capsule.
27. A plurality of capsules and chain links of any one of claims 3 to 26, wherein the chain links are pivotally connected to the capsules to form chain linked capsules according to claim 1 or claim 2.
- 20 28. The plurality of capsules and chain links of claim 27 provided within a channel.
29. An inhalation device containing chain-linked capsules which contain an inhalable product.
30. Chain linked capsules substantially as hereinbefore described with
25 reference to Figures 3 and 4 or Figures 3 and 5 of the accompanying drawings.

ABSTRACT

CHAIN LINKED CAPSULES

5

Chain linked capsules comprising multiple capsules (10) interconnected in a chain by chain links (32).

10

The capsules comprise a sleeve (16) and a piston (14) whereby a powder product can be sealed within the capsule (10).

15

The capsules (10) are for use in inhalation devices, for example for entraining a dose of an inhalable pharmaceutical powder product to a patient's respiratory tract.

20

Figure 4 to accompany the abstract upon publication.

1/2




FIG 1




FIG 2




FIG. 3




FIG 4




FIG 5

PCT/EP2004/004007



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.